

Product Data Sheet

YDN385 | Fully Waterborne High Imino Methyl Etherified Melamine Resin

Ydnresin | A Division of YDN Group

 Last Updated: May 2025

1. Product Description

YDN385 is a **fully water-soluble**, partially methyl etherified melamine formaldehyde resin, engineered for use as a **crosslinking agent in water-based coating systems**. It features **high imino and hydroxymethyl functionality**, delivering fast self-condensation, improved film hardness, and strong compatibility with a broad range of anionic emulsions and polymer dispersions.

2. Key Features

- Fully soluble in water (zero solvent)
- High imino group content — enhances reactivity and hardness
- Excellent compatibility with acrylics, polyesters, emulsions
- Low free formaldehyde ($\leq 0.5\%$) for safer use
- Stable at neutral to mildly alkaline pH (8.5–9.5)
- Cures with mild acid catalyst (organic or inorganic)
- Improves film resistance to heat and plastic deformation
- Reduces VOC emission compared to solvent-based crosslinkers

3. Typical Applications

- Waterborne wood coatings
- Emulsion-based industrial and decorative topcoats
- Acrylic, polyester, alkyd emulsions
- Eco-friendly OEM and furniture coatings
- Water-soluble dispersion systems for metal or plastic

4. Technical Specifications

Property	Value
Appearance	Transparent viscous liquid
Solvent	Water
Solid Content (105°C × 3h)	≥78%
Viscosity (30°C)	800–1500 mPa·s
Density (23°C)	~1250 kg/m³
Flash Point (closed cup)	>100°C
Free Formaldehyde Content	≤0.5%
pH (1:1 solution with water)	8.5–9.5
Shelf Life	6 months (sealed, cool storage)

5. Solubility Profile

Solvent Type	Solubility
Water	 Fully Soluble
Alcohols	 Partially Soluble
Ketones	 Not Soluble

Solvent Type	Solubility
Esters	✗ Not Soluble
Aliphatic Hydrocarbons	✗ Not Soluble
Aromatics	✗ Not Soluble

6. Polymer Compatibility

Polymer Type	Compatibility
Waterborne Acrylic	✓ Excellent
Polyester Dispersion	✓ Excellent
Alkyd Emulsions	✓ Good
Polyurethane Emulsions	✓ Good
Epoxy Waterborne Systems	⚠ Moderate

7. Packaging

- 20L HDPE Drum
- 200L Steel Drum
- 1000L IBC Tote

8. Storage & Handling

- Store in **cool, dry, well-ventilated** environments
- Avoid direct sunlight and extreme temperatures

- Keep container tightly sealed
- Shelf life: **6 months** when stored at $\leq 25^{\circ}\text{C}$ in original packaging
- Use appropriate **PPE**: gloves, goggles, protective clothing

9. Contact Information

Ydnresin | A Division of YDN Group

- 📍 No. 2088, Jiuliting Avenue, Caoqiao Street, Pinghu City, Zhejiang Province, China
- ✉️ Email: sales@ydnresin.com
- 📞 Phone / WhatsApp: +86-135-4070-2776 | +86-135-8634-6868
- 🌐 Website: www.ydnresin.com